



motorola



hellosecurity

MTIBM032704

2MP IP Bullet Face Detection Starlight Camera

General features:

1/2.8" CMOS Starlight sensor

2MP high resolution

Supports H.265+ / H.265 / H.264+ / H.264

Intelligent Analytics: Face detection, Video blur detection, scene change detection, Human/Vehicle line crossing detection, Human/Vehicle region intrusion detection, Target line/area counting

IP67 Ingress protection

Automatic ICR

3D DNR, HLC, BLC, Defog

120dB WDR

ROI Coding

1 channel Audio input

Supports micro-SD card for storage of up to 256GB

30m IR infrared night view distance

POE



ONVIF Profile S & G compliant



Model: MTIBM032704

Camera	
Camera Type	Mini Bullet
Image Sensor	1/2.8" Starlight CMOS
Lens	Fixed 2.8mm @ F1.6, horizontal field of view: 108°
Mount Type	M12
Scanning System	Progressive
Image Size	1920 × 1080
Iris Type	Fixed
Electronic Shutter Speed	NTSC: 1s~1/100,000s PAL: 1s~1/100,000s
Minimum Illumination	0.005 lux @F1.6, AGC ON; 0 lux with IR
IR Distance	30m
Angle Adjustment	Pan: 0° ~ 360°; Tilt: 0° ~ 80°; Rotation: 0° ~ 360°
Video	
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, (480 × 240)
Video Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Image System	NTSC / PAL
Frame Rate	Main Stream: NTSC: 60Hz : 1080P / 720P (1~30fps) PAL: 50Hz : 1080P / 720P (1~25fps)
	Sub Stream: NTSC: 60Hz : 720P / D1 / CIF / (1~30fps) PAL: 50Hz : 720P / D1 / CIF / (1~25fps)
	Third Stream: NTSC: 60Hz : D1 / CIF / (1~30fps) PAL: 50Hz : D1 / CIF / (1~25fps)
Stream Capability	3 Streams
High Frame Rate Mode	No
Bit Rate	64 Kbps ~ 6 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
BLC	Yes
HLC	Yes
WDR	120dB
Defog	Yes
AGC	Yes
Noise Reduction	3D DNR
Day/Night	Automatic ICR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI	Each ROI can be configured separately
Motion Detection	Yes
Privacy Masking	Max. 4 Areas
Mirror	No
Flip	No
Software & Network	
Remote Monitoring	Web browsing, MVMS, hellosecurity APP
Management Software	MVMS Lite, Standard, Professional
Mobile APP	iOS, Android
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, HTTPS, SNMP, 802.1X, QoS
Interoperability	ONVIF (Profile S/Profile G), P2P
Bandwidth Self-adaptation	Yes
Browser	IE (plug-in required) / Google Chrome / Edge / Firefox / Safari
Interfaces	
Video Output (CVBS)	No
Audio In/Out	1/0
Alarm In/Out	0/0
Built in Mic	No
RS485	No
Hardware Reset	Yes
Micro SD Card Slot	Yes (up to 256GB)
Ingress Protection	IP67
Vandal Resistance	IK10 only housing
Network	RJ45 10/100 Mbps
Functions	
Smart Alarm	Motion detection; Sensor alarm; SD card error; SD card full; IP conflict; Network disconnection
Intelligent Analytics	Line crossing, intrusion (human/motor vehicle/non-motor vehicle classification), Face detection, Target line/area counting, video blur, scene change
General function	Watermark, IP address filtering, video mask, heartbeat, password protection

hellosecurity



Others	
Power Supply	DC12V / PoE (802.3af)
Power Consumption	< 6.5W
Operating Environment	-30°C ~ +60°C Humidity: less than 95% (non condensing)
Casing	Metal
Dimensions (mm)	167.5 x 74.5 x 74.5
Weight (net)	Approx. 0.42kg