



motorola



hellosecurity

2MP Varifocal IP Dome Camera

MTIDM052715

General characteristics:

2MP (1920 × 1080) high resolution

Manual Varifocal 2.8 ~ 12mm lens

1/2.8" CMOS image sensor

H.265+ /H.265 / H.264+/ H.264/ MJPEG coding

50m Infrared night view distance

Intelligent Analytics: Line Crossing, Intrusion, Object Removed Detections, Exception

3D DNR, digital WDR, HLC, BLC, Defog

Smart IR and ROI coding

Built-in Microphone

Auto ICR, true day/night

IP67 Ingress Protection

Works with PoE

ONVIF Profile S and Profile G





motorola

Model: MTIDM052715

Camera	
Camera Type	Dome
Image Sensor	1/2.8" CMOS
Lens	Manual Varifocal 2.8mm ~ 12mm @ F1.6, horizontal field of view: 102° ~ 33°
Mount Type	Φ14
Scanning System	Progressive
Image Size	1920×1080
Iris Type	Fixed
Electronic Shutter Speed	NTSC: 1/3s~1/100,000s PAL: 1/3s~1/100,000s
Minimum Illumination	0.008 lux @ F1.6, AGC ON; 0 lux with IR
IR Distance	50m
Angle Adjustment	Pan: 0° ~ 360°; Tilt: 0° ~ 90°; Rotation: 0° ~ 360°
Video	
Resolution	2MP (1920 x 1080), 720P (1280 x 720), D1, CIF (480 x 240)
Video Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Image System	NTSC / PAL
Frame Rate	Main Stream: NTSC: 60Hz : 1080P / 720P (1~30fps)
	PAL: 50Hz : 1080P / 720P (1~25fps)
	Sub Stream: NTSC: 60Hz : D1 / CIF / (1~30fps) PAL: 50Hz : D1 / CIF / (1~25fps)
Stream Capability	2 Streams
High Frame Rate Mode	No
Bit Rate	128 Kbps ~ 4 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	N/A
BLC	Yes
HLC	Yes
WDR	Digital
Defog	Yes
AGC	Yes
Noise Reduction	DNR
Day/Night	Automatic ICR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI	Each ROI can be configured separately
Motion Detection	Yes
Privacy Masking	Max. 4 Areas
Mirror	Yes
Flip	Yes
Software & Network	
Remote Monitoring	Web browsing, MVMS, hellosecurity APP
Management Software	MVMS Lite, Standard, Professional
Mobile APP	iOS, Android
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Protocol	TCP/IP UDP DHCP NTP RTSP PPPoE DDNS SMTP FTP, HTTPS, SNMP, 802.1X, QoS
Interoperability	ONVIF (Profile S & Profile G), P2P
Bandwidth Self-adaptation	Yes
Browser	IE (plug-in required)/Google Chrome/Edge/Firefox/Safari
Interfaces	
Video Output (CVBS)	No
Audio In/Out	1/0
Alarm In/Out	0/0
Built in Mic	Yes
RS485	No
Hardware Reset	Yes
Micro SD Card Slot	Yes, (up to 256GB)
Ingress Protection	IP67
Vandal Resistance	IK10 housing only
Network	RJ45 10/100 Mbps
Functions	
Smart Alarm	Motion detection; Sensor alarm; IP conflict; Network disconnection
Intelligent Analytics	Line Crossing, Intrusion, Exception
General function	Watermark, IP address filtering, video mask, heartbeat, password protection
Others	
Power Supply	DC12V / PoE (802.3af)
Power Consumption	< 7W
Operating Environment	-30°C ~ +60°C Humidity: less than 95% (non condensing)
Casing	Metal
Dimensions (mm)	Φ 111.5 × 99.6
Weight (net)	Approx. 0.65kg

hellosecurity



DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	43.13m(141.50ft)	17.25m(56.59ft)	8.63m(28.31ft)	4.31m(14.14ft)
2.8~12mm(T)	131.90m(432.74ft)	52.76m(173.09ft)	26.38m(86.54ft)	13.19m(43.27ft)